

WAP-POWER-48J90



48V/90W AC to DC POWER ADAPTOR FOR
WAC/WPC/WAS SERIES PRODUCTS

Features

- Universal input 90 to 264 VAC
- Short circuit, overload, over voltage, over temperature protected
- EMI meets FCC Part 15 Class B /CISPR 22 Class B
- CE Marked and CB Certificated
- RoHS Compliant

Specification

Output

Voltage: 48V
Rated Current: 1.875A
Rated Power: 90W

Input

Voltage Range: 100~240VAC
Frequency: 50/60Hz
Inrush Current: 40A max. / 115VAC (Cold Start);
80A max. / 230VAC (Cold Start)

Protection

Overvoltage Protection: Auto-recovery
Overload Protection: Auto-recovery
Short Circuit Protection: Auto-recovery
Leakage Current: 3.5mA max.(Class I)

Dimension & Weight

Dimension: 148(W)x59(L)x32(H)mm
Weight: 550g

Environmental Condition

Working Temperature Range: 0°C~40°C
Humidity: 5~95% RH non-condensing
Storage Temperature Range: -40°C~85°C

Safety & EMI Regulations

UL 60950 / cUL 60950 / TUV EN60950 / CB Certificate / CE Marked / FCC Part15 Class B / CISPR 22 Class B / EN55022 Class B / EN61000-3-3

Order Information

POWER ADAPTOR ACCESSORY FOR WAC/WPC/WAS SERIES PRODUCTS		
WAP-POWER-48J90	48V/90W AC to DC POWER ADAPTOR FOR WAC/WPC/WAS SERIES PRODUCTS	(US/UK/AU/EU standards are available)