



MWR-3102-AX54

1 x 1/2.5GBase-T RJ-45 +

1 x 1000MBase-T RJ-45

Dual-Band AX5400 Mesh Wi-Fi 6 Router

Description

Connection Technology Systems (CTS) MWR-3102-AX54 is a dual-band mesh Wi-Fi router equipped with 1 x 1/2.5GBase-T and 1 x 1000MBase-T RJ-45 ports.

Fully compliant with IEEE 802.11a/b/g/n/ac/ax standard, the next-generation Wi-Fi 6 router delivers both wireless frequency bands of 2.4GHz and 5GHz. The two bands deliver less connection interference from solid obstructing objects as well as boost the data transmission rate that covers the increasing higher-bandwidth demand.

Featured with a host of up-to-date technologies, MWR-3102-AX54 utilizes a modulation scheme of 1024-QAM optimizing spectral efficiency, which translates to better throughput and strengthens the data capacity by up to 25%. The OFDMA, a modulation technique as well, makes wireless APs capable of channel partitioning and allocation, maximizing bandwidth efficiency and minimizing wireless network latency from poor resource utilization, whereas the 160 MHz Wi-Fi channel addresses the network speed insufficiency in the face of what modern-day ultra-HD streaming and gaming necessitate.

The Wi-Fi mesh system feature blankets your home with a Wi-Fi connection. Worry no more about getting caught up on network dead zones while bouncing from room to room at home. And enjoy uninterrupted wireless connectivity unlike before.

The 2.5G Ethernet port satisfies the needs of the connection speed for modern-day, bandwidth-demanding gadgets.

For management, monitoring, and Wi-Fi optimization, they can all be done remotely through CWMP TR-069/181. The centralized control fulfills task automation and remote management, simplifying firmware updates and security-breach patching.

The Wi-Fi management app available on iOS and Android systems enables users to tailor and personalize a whole-home Wi-Fi network to one's needs and facilitates the efficiency of maintenance and troubleshooting that are otherwise tricky at times.

Features

■ Wi-Fi 6 Technology

Incorporate Wi-Fi 6 technologies including OFDMA, MU-MIMO, 1024-QAM, and 160MHz Wi-Fi channel, which maximize bandwidth efficiency, strengthen data capacity, and boost up data transmission rate.

■ Dual-Band 4x4 (5GHz) and 2x2 (2.4GHz)

Compliant with the up-to-date Wi-Fi 6 standard, the 5GHz 4x4 + 2.4GHz 2x2 design enables the users to get up to the faster connection speed and to enjoy the extensive Wi-Fi coverage, enhancing the whole-home wireless entertainment and smart home experience.

■ High-Speed 2.5G Ethernet Port

The 2.5G Ethernet port brings you the faster-than-1Gbps network connection for modern-day, bandwidth-demanding gadgets.

■ Whole-Home Mesh System

The mesh system blankets your home with a Wi-Fi connection. Worry no more network dead zones while bouncing from room to room at home, and enjoy uninterrupted wireless connectivity unlike before.

■ Android/iOS Wi-Fi App

The mobile app available on iOS and Android systems enables users to tailor and personalize a whole-home Wi-Fi network to one's needs and facilitates the efficiency of maintenance and troubleshooting that are otherwise tricky at times.

■ CWMP TR-069/181 Compliant

The centralized control fulfills task automation and remote management, simplifying firmware updates and security-breach patching. For management, monitoring, and Wi-Fi optimization, they can all be done remotely through CWMP TR-069/181.

■ Dual Image, Double Reliability

A fail-safe mechanism that prevents the device from crashing and malfunctioning upon a firmware upgrade or update, allowing the system to switch between them in case of a corrupted image.

■ WPA3 Security

The Wi-Fi security protocol, WPA3, brings new capabilities to improve cybersecurity and more robust encryption of the Wi-Fi password safety, hence enhancing protection against brute-force attacks or packet-eavesdropping to safeguard your home Wi-Fi network.

Specification

■ Interface

- 1 x 1000MBase-T RJ-45
- 1 x 1/2.5GBase-T RJ-45
- 1 x USB 2.0
- 1 x WPS Button
- 1 x Reset Button

■ Routing

- WAN Connection Type: DHCP, Static IP, PPPoE
- NAT
- IPv6/IPv4
- DHCPv6
- Dynamic DNS

■ Wi-Fi

Wi-Fi Characteristics

- IEEE 802.11ax/ac/n/a 5GHz
- IEEE 802.11ax/n/b/g 2.4GHz
- IEEE 802.11k/v
- Wireless:
 - Internal Antenna 4x4 (5GHz) + 2x2 (2.4GHz)
 - 802.11ax (2.4GHz): Up to 574Mbps
 - 802.11ax (5GHz): Up to 4804Mbps
- Channel Bonding:
 - 20/40MHz for 2.4GHz
 - 40/80/160MHz for 5GHz
- 1024-QAM
- OFDMA

Wi-Fi Features

- 2 x SSID (Main / Guest)
- Wireless AP Mode
- Wi-Fi Multimedia (WMM)
- Airtime Fairness (ATF)
- Wi-Fi Protected Setup (WPS)
- Auto Channel Selection
- MU-MIMO and Beamforming
- Band Steering

Wi-Fi Security

- 64/128-bit WPA2/WPA3 Data Encryption
- Firewall
- Device Access Control

■ Network

- IEEE 802.1q Tag VLAN
- Client Info

■ Management

- HTTP / HTTPS
- TR-069/181
- Android / iOS App
- Network Map
- Mesh Management
- Event Log / Syslog
- Ping / Traceroute
- Firmware Upgrade
- Dual Image

■ Parental Controls

- Time Controls
- Pause Internet

■ Power Requirement

- Input Power: 12VDC, 2A
- Max. Power Consumption: 24W (82BTU/h)

■ Environmental Condition

- Operation: 0°C ~ 40°C
- Storage: -20°C ~ 70°C


■ Dimension

- Size: 70 x 160 x 150mm (W x D x H)
- Weight: 650g

■ EMC/Safety

- FCC Class B, CE, UKCA

Application Diagram



Order Information

Model	TP Port		TP Port		Support Power Source
	Speed	Port	Speed	Port	
MWR-3102-AX54	1G	1	1/2.5G	1	External power adapter

Connection Technology Systems Inc. (HQ)
 Tel.: +886-2-2698-9661
 E-mail: cts_esales@ctsystem.com
 info@ctsystem.com
 Sales Direct Line: +886-2-26989201

Connection Technology Systems NE AB
 Tel: +46-31-221980
 E-mail: info@ctsystem.se

Connection Technology Systems Central Europe (COMPONET Handels GmbH)
 Tel: +43-1-235 05 66-0
 E-mail: cts_ce@ctsystem.com



Connection Technology Systems Japan
 Tel: +81-6-6450-8890
 E-mail: cts_japan@ctsystem.com

Connection Technology USA Inc.
 Tel: +1-510-509-0304
 Sales Direct Line: +1-510-509-0305
 E-mail: cts_us@ctsystem.com

Connection Technology Systems India Private Limited
 E-mail: kirti_simha@ctsystem.com



Connection Technology Systems (CTS) reserves the right to change specification without prior notice.